

List of Figures

Figure 2-1	Historical Trend in the Number of New BRTs	11
Figure 2-2	Number of Cities with BRTs (per region) and BRT Length (km)	12
Figure 2-3	Number of BRTs, by country	13
Figure 2-4	BRTs' Length, by country	13
Figure 2-5	Bogota's Transport System Reform: Before and After	16
Figure 2-6	Number of Passengers, per day	17
Figure 2-7	Number of Passengers, per day per capital cost	17
Figure 2-8	Modal Share	18
Figure 2-9	Travel Speed of Passenger Vehicles in Seoul and CBD (1996–2010)	22
Figure 2-10	Modal Share in Seoul (1996–2010)	23
Figure 3-1	Marginal Utility Concept on BRT Service	31
Figure 3-2	Total Utility and Preference to Shift	31
Figure 3-3	Increasing Utility to Promote Modal Shift	32
Figure 3-4	No Transfer Scenario	33
Figure 3-5	One Transfer Scenario	33
Figure 3-6	15 Minutes' Transfer Time	34
Figure 3-7	10 Minutes' Transfer Time	34
Figure 3-8	Five Minutes' Transfer Time	34
Figure 3-9	Existing Infrastructure	35
Figure 3-10	Sterile Dedicated Lane	35
Figure 3-11	Passing Place	36
Figure 3-12	Bus Priority Signal	36
Figure 3-13	Origin–Destination Zone	37
Figure 3-14	Existing Condition of TransJakarta Corridor 3	39
Figure 3-15	15 Minutes' Transfer Time	40
Figure 3-16	Existing Travel Time = 60 Minutes	40
Figure 3-17	Example of Stated Preference Questionnaire	40
Figure 3-18	Logit Model Illustration	41
Figure 3-19	First Priority for Improvement	43
Figure 3-20	Second Priority for Improvement	43
Figure 3-21	Third Priority for Improvement	44
Figure 3-22	Reasons for Using TransJakarta or Private Car	44
Figure 3-23	Mode Needed from Home to Shelter and from Shelter to Last Destination	45
Figure 3-24	Response to Reduced Travel Time – Pessimistic Scenario	46
Figure 3-25	Response to Reduced Travel Time – Pessimistic Scenario	47

	(Sensitivity Analysis)	
Figure 3-26	Response to Reduced Travel Time – Moderate Scenario	48
Figure 3-27	Response to Reduced Travel Time – Moderate Scenario (Sensitivity Analysis)	49
Figure 3-28	Response to Reduced Travel Time – Optimistic Scenario	50
Figure 3-29	Response to Reduced Travel Time – Optimistic Scenario (Sensitivity Analysis)	51
Figure 3-30	Logit Model Result Summary Illustration	52
Figure 4-1	TransJakarta Route Map	60
Figure 4-2	Overview of Corridor 3	61
Figure 4-3	No. of Passengers/Day (weekdays) from Each Station in 2009	61
Figure 4-4	Process of GPS Data Compilation	62
Figure 4-5	Example of Time–Space Graph	63
Figure 4-6	Histogram of the Operation Frequency on Weekdays and on Holidays	64
Figure 4-7	Histogram of Travel Time from Kalideres to Harmoni on Weekdays and on Holidays	65
Figure 4-8	Average Speed between Each Pair of Stations and Average Travel Time on Holidays and on Weekdays	66
Figure 4-9	Locations for the Implementation of Improvement Measures	68
Figure 4-10	Illustration of “Total Elevation” in Case D	69
Figure 4-11	Selected Origin–Destination Zones	71
Figure 4-12	Ratio of Target Traffic Amounts in Each Road Section	71
Figure 4-13	Reduced Trip Time for Each Origin–Destination	72
Figure 4-14	Rate of Modal Shift for Each Measure	73
Figure 4-15	Amount of Modal Shift for Each Measure	73
Figure 4-16	Rate of Fuel Consumption when Driving an Automobile	74
Figure 4-17	Amount of Fuel Consumption Reduction for Each Measure	75
Figure 4-18	Average Speed for Private Transport	76
Figure 4-19	Decrease in Fuel Consumption if Applied to 12 Corridors	77
Figure 4-20	Decrease in Fuel Consumption if Applied to 30 Corridors	77
Figure 4-21	Cost Required for a Decrease in Fuel of 1toe/yr	78
Figure B-1	Distribution of Number of Days for Average Speed between Pairs of Stations on Weekdays	92
Figure B-2	Distribution of Number of Days for Average Speed	94

	between Pairs of Stations on Holidays	
Figure D-1	Operating Table for Current Case	98
Figure D-2	Operation Table for Case A	99
Figure D-3	Operation Table for Case B	99
Figure D-4	Operation Table for Case C	100
Figure D-5	Operation Table for Case D	100